



**Materials:**

- Inner Core: Stainless Steel
- Housing & Base: Aluminum
- Resilient Element: Steel Cushion

**Operating Temperature:**

- -100°F to 400°F

**Natural Frequency:**

- 12 to 15 Hz

**Weight:**

- 0.65 to 0.75 oz.

| Part Number | Load Rating (lbs.) | Transmissibility at Resonance | Dimensions in inches |      |       |       |       |       |      |      |
|-------------|--------------------|-------------------------------|----------------------|------|-------|-------|-------|-------|------|------|
|             |                    |                               | A                    | B    | C     | D     | E     | F     | G    | H    |
| WM9301-1    | 0.5 — 1            | 4                             | 0.94                 | 1.25 | 1.000 | 0.221 | 0.141 | 0.047 | 0.80 | 1.50 |
| WM9301-2    | 1 — 2              |                               |                      |      |       |       |       |       |      |      |
| WM9301-3    | 2 — 3              |                               |                      |      |       |       |       |       |      |      |
| WM9302-1    | 1 — 2              | 4                             | 1.22                 | 1.75 | 1.375 | 0.281 | 0.196 | 0.188 | 1.09 | 2.00 |
| WM9302-2    | 1.75 — 3.5         |                               |                      |      |       |       |       |       |      |      |
| WM9302-3    | 3.25 — 6.5         |                               |                      |      |       |       |       |       |      |      |
| WM9303-1    | 2 — 3              | 4                             | 1.56                 | 1.97 | 1.375 | 0.344 | 0.196 | 0.188 | 1.25 | 2.31 |
| WM9303-2    | 3 — 5              |                               |                      |      |       |       |       |       |      |      |
| WM9303-3    | 5 — 7              |                               |                      |      |       |       |       |       |      |      |
| WM9303-4    | 7 — 10             |                               |                      |      |       |       |       |       |      |      |
| WM9303-7    | 10 — 13            |                               |                      |      |       |       |       |       |      |      |
| WM9304-1    | 1 — 2              | 4                             | 1.94                 | 2.25 | 1.750 | 0.344 | 0.196 | 0.188 | 1.25 | 2.31 |
| WM9304-2    | 7 — 11             |                               |                      |      |       |       |       |       |      |      |
| WM9304-3    | 11 — 16            |                               |                      |      |       |       |       |       |      |      |
| WM9304-4    | 4.5 — 7            |                               |                      |      |       |       |       |       |      |      |
| WM9304-5    | 2 — 2              |                               |                      |      |       |       |       |       |      |      |
| WM9304-6    | 3 — 4.5            |                               |                      |      |       |       |       |       |      |      |

**Table 1: Values for Dimensions in Drawing & Performance Characteristics**